



Specifications

Camera Type	Bullet
Image Sensor	1/2.7" Progressive CMOS
Maximum Video Resolution (Megapixels)	5
Maximum Video Resolution	2592 x 1944
Lens	2.8 mm (H.FOV: 92°)
Lens Type	Fixed
Maximum Night IR Distance (M)	20
Image clarity	3
Connectors	RJ-45
Video Compression	H.265, H.264
ONVIF (depends on firmware version)	2.6
Operating Environment	-10°C to 55°C (14°F-131°F) Humidity: 20%-80% RH
Dimensions	70mm×155mm
Weight (Net)	0.44
Accessories	IV2422X, IV2477X
Power Supply	Power over Ethernet IEEE 802.3af, DC12V
Power Consumption	4.2 W
Connectors (web)	RJ-45 , DC Power Input
Outdoor Use	Yes
IP Rating	IP66
Vandal Resistant	Yes
Frame Rate at Resolution	15
Day/Night Mode	Auto
Image Enhancement	Flip mode, Brightness, Contrast, Saturation, Sharpness, Hue
Edge Recording Slot	Micro SD/SDHC Card
Video Compression	H.265, H.264 (3 streams)
Audio Streaming	Yes (microphone and speaker included)
Protocols	TCP/IP, UDP, HTTP, HTTPS, DHCP, FTP, RTP/RTSP, DNS, DDNS, NTP, PPPOE, UPNP, SMTP, SNMP, P2P (QR code)
Software	Device Search/Config Tool, Surveillance Client (CMS/VMS), Mobile app
Power Over Ethernet	Yes
Ethernet	Ethernet (10/100 Base-T)
UPNP	Yes
In The Box	Free Software available from FAQ, Printed quick user guide, installation template, mounting screws and plugs
Warranty	3 Year Warranty
Weight (Packaged)	0.55